

CLASSIC BLUE POWER battery series is a range of starter batteries designed with the latest technologies technical solutions and are dedicated to standardly equipped vehicles and passenger cars. Batteries offer high quality and reliability. Thanks to use of plates based on grids made of calcium alloys with a high tin content, battery achieves excellent operational features. Additionally water loss is minimized, what makes CLASSIC BLUE POWER battery completely maintenance-free. Internal resistance decreased and increased acceptance of the battery charge, allowed us to obtain a product with excellent cyclic durability and great parameters.

CLASSIC BLUE POWER batteries are produced using modern technology charging technique based on electrolyte recirculation formation and bath formation. Temperature stabilization in the battery formation process guarantees proper composition of the active mass, which is extremely important to achieve required electrical parameters of the battery. CLASSIC BLUE POWER batteries are products with the right price-quality ratio.

Characteristics:

- · Calcium-Calcium technology
- a design that eliminates the possibility of top short circuits
 pole terminals made by "Hot-Rod" technology
- charged in thermostated conditions
- minimized water consumption
- maintenance free
- economical construction



Battery code	Capacity [Ah]	Polarity	Starting current EN [A]	Dimensions [mm] Length/width/height
R042560AB	42	[- +]	330	175 x 175 x 190
R044560AB	44	[- +]	390	175 x 175 x 190
R045612AB	45	[- +]	360	207 x 175 x 190
R045613AB	45	[+ -]	360	207 x 175 x 190
R045620AB	45	[- +]	360	207 x 175 x 175
R050612AB	50	[- +]	450	207 x 175 x 190
R055614AB	55	[- +]	460	242 x 175 x 190
R055615AB	55	[+ -]	460	242 x 175 x 190
R062614AB	62	[- +]	510	242 x 175 x 190
R062615AB	62	[+ -]	510	242 x 175 x 190
R062622AB	62	[- +]	510	242 x 175 x 175
R074616AB	74	[- +]	680	276 x 175 x 190
R074624AB	74	[- +]	680	276 x 175 x 175
R080660KN	80	[- +]	700	315 x 175 x 175
R088636KN	88	[- +]	720	352 x 175 x 190
R092636AB	92	[- +]	740	352 x 175 x 190
R100636KN	100	[- +]	780	352 x 175 x 190
R110686K	110	[- +]	920	352 x 175 x 190

Advantages:

- product with right price-quality ratio
- startup guaranteed in any conditions extended cycle life
 - reduced self-discharge effect
- minimal water loss during operation
 - maintenance-free according to EN
 - safety of use





